



THE TOURISMO.

Technical data and equipment at
a glance.

Mercedes-Benz

The standard for buses.



THE TOURISMO AT A GLANCE.

Tourismo L



Length [mm]: 13,935
Turning circle [mm]: 23,327

Height [mm]: 3,680
Width [mm]: 2,550

Tourismo M/3



Length [mm]: 13,115
Turning circle min. [mm]: 21,428

Height [mm]: 3,680
Width [mm]: 2,550

Tourismo M/2



Length [mm]: 13,115
Turning circle min. [mm]: 23,774

Height [mm]: 3,680
Width [mm]: 2,550

Tourismo



Length [mm]: 12,295
Turning circle min. [mm]: 21,634

Height [mm]: 3,680
Width [mm]: 2,550

TECHNICAL DATA AND EQUIPMENT AT A GLANCE.

	Tourismo L	Tourismo M/3	Tourismo M/2	Tourismo
Transport capacity				
Number of seats – standard seating	1/59	1/55	1/55	1/51
Passenger capacity min.	48	44	44	44
Passenger capacity max.	65	59	55	55
Seating type Travel Star Eco (TSE)	●	●	●	●
Seating type Travel Star Eco (TSE) Softline	○	○	○	○
Seating type Travel Star Eco (TSE) Luxline	○	○	○	○
Seating type Travel Star Xtra (TSX)	○	○	○	○
Driver's seat GRAMMER Linea MSG 90.6 P, air-sprung	●	●	●	●
Driver's seat ISRI 6860, integrated pneumatic system, 3-point seat belt	○	○	○	○
Wheelchair space	○	○	○	○

	Tourismo L	Tourismo M/3	Tourismo M/2	Tourismo
Dimensions				
Length [mm]	13,935	13,115	13,115	12,295
Length incl. mirrors [mm]	14,296	13,476	13,476	12,656
Width [mm]	2,550	2,550	2,550	2,550
Height [mm]	3,680	3,680	3,680	3,680
Inner stand height [mm]	2,014	2,014	2,010	2,010
Inner stand height central aisle [mm]	2,014	2,014	2,010	2,010
Wheelbase front axle-drive axle [mm]	6,910	6,090	6,910	6,090

	Tourismo L	Tourismo M/3	Tourismo M/2	Tourismo
Wheelbase drive axle - trailing axle [mm]	1,350	1,350	-	-
Tyre size	295/80 R 22,5	295/80 R 22,5	295/80 R 22,5	295/80 R 22,5
Overhang at front [mm]	2,890	2,890	2,890	2,890
Overhang at rear [mm]	2,785	2,785	3,315	3,315
Turning circle [mm]	23,327	21,428	23,774	21,634
Turning circle min. [mm]	23,327	21,428	23,774	21,634
Track circle minimal [mm]	19,190	17,252	19,589	17,45
Wheel impact front axle max. [°]	54	54	54	54
Swing-out dimension [mm]	1,126	1,186	649	719
Usable volume / capacity AdBlue [l]	35 / 40	35 / 40	35 / 40	35 / 40
Capacity fuel tank left / right [l]	260 / 220	260 / 220	260 / 220	260 / 220
Luggage compartment volume [m ³]	12.1	9.9	12.1	9.9
Additional storage area volume [m ³]	1.15	1.35	1.6	1.5
Floor height central aisle over roadway [mm]	1,370	1,370	1,370	1,370
Pedestal height [mm]	150	150	150	150
Entry height door 1 [mm]	355	355	355	355
Entry height door 2 [mm]	365	365	365	365
Door opening width 1 [mm]	770	770	770	770
Door opening width 2 [mm]	590-650	900	590-650	590-650

	Tourismo L	Tourismo M/3	Tourismo M/2	Tourismo
Doors and glazing				
Number of doors	2	2	2	2
Outward swiveling door	●	●	●	●
Door position (A or B)	A	A	A	A
Lift	○	○	●	○
Double glazed	●	●	●	●
Windscreen heatable	○	○	○	○
Windscreen Opticool	●	●	●	●

	Tourismo L	Tourismo M/3	Tourismo M/2	Tourismo
Transmission				
Engine	Mercedes-Benz OM 470	Mercedes-Benz OM 470	Mercedes-Benz OM 470	Mercedes-Benz OM 470
Engine 2*	Mercedes-Benz OM 470	Mercedes-Benz OM 470	Mercedes-Benz OM 470	Mercedes-Benz OM 470
Engine 3*	Mercedes-Benz OM 470	Mercedes-Benz OM 470	Mercedes-Benz OM 470	Mercedes-Benz OM 470
Engine 4*	-	Mercedes-Benz OM 470	Mercedes-Benz OM 470	Mercedes-Benz OM 470
Engine type	6-cylinder in-line-engine	6-cylinder in-line-engine	6-cylinder in-line-engine	6-cylinder in-line-engine
Output [kW]	290	290	265	265
Output 2* [kW]	315	265	290	290
Output 3* [kW]	335	315	315	315
Output 4* [kW]	-	335	335	335
Max. torque [Nm]	1,900	1,700	1,700	1,700
Max. torque 2* [Nm]	2,100	1,900	1,900	1,900
Max. torque 3* [Nm]	2,200	2,100	2,100	2,100
Max. torque 4* [Nm]	-	2,200	2,200	2,200
At speed [1/min]	1,100	1,100	1,100	1,100

	Tourismo L	Tourismo M/3	Tourismo M/2	Tourismo
At speed 2* [1/min]	1,100	1,100	1,100	1,100
At speed 3* [1/min]	1,100	1,100	1,100	1,100
At speed 4* [1/min]	-	1,100	1,100	1,100
Displacement [l]	10.7	10.7	10.7	10.7
Displacement 2* [l]	10.7	10.7	10.7	10.7
Displacement 3* [l]	10.7	10.7	10.7	10.7
EU emissions standard	Euro VI E	Euro VI E	Euro VI E	Euro VI E
Transmission	Mercedes-Benz GO 210-6	Mercedes-Benz GO 210-6	Mercedes-Benz GO 210-6	MB GO 190-6
Transmission 2*	ZF Ecolife AP	ZF Ecolife AP	Mercedes-Benz GO 250-8	Mercedes-Benz GO 210-6
Transmission 3*	Mercedes-Benz GO 250-8	Mercedes-Benz GO 250-8	ZF Ecolife AP	Mercedes-Benz GO 250-8
Transmission 4*	-	Mercedes-Benz GO 230-6	Mercedes-Benz GO 190-6	ZF Ecolife AP

	Tourismo L	Tourismo M/3	Tourismo M/2	Tourismo
Chassis				
Steering	ZF 8098 Servocom	ZF 8098 Servocom	ZF 8098 Servocom	ZF 8098 Servocom
Front axle, type	ZF RL 82 EC			
Driven axle, type	Mercedes-Benz RO 440	Mercedes-Benz RO 440	Mercedes-Benz RO 440	Mercedes-Benz RO 440
Front axle: independent suspension, anti-roll bar	●	●	●	●
Drive axle: with anti-roll bar	●	●	●	●
Trailing axle: active steering, independent suspension	●	●	-	-
Raising/Lowering system	●	●	●	●
Kneeling	○	○	○	○
Air suspension via electronic level control system (ENR)	●	●	●	●

	Tourismo L	Tourismo M/3	Tourismo M/2	Tourismo
Brakes				
Pneumatic disc brakes on all axles	●	●	●	●
Electronic Stability Programme (ESP®)	●	●	●	●
Electronically controlled braking system (EBS)	●	●	●	●
Anti-locking system (ABS)	●	●	●	●
Brake Assist (BAS)	●	●	●	●
Acceleration Slip Regulation (ASR)	●	●	●	●
Retarder limiter (RL)	●	●	●	●
Retarder	Secondary water retarder (SWR)			
Automatic bus stop brake with pull-away lock	○	○	○	○
Parking brake	●	●	●	●

	Tourismo L	Tourismo M/3	Tourismo M/2	Tourismo
Safety and driver assistance systems				
Rollover strength compliant with in ECE R29	●	●	●	●
Adaptive Cruise Control (ART)	○	○	○	○
Lane Assist (SPA)	●	●	●	●
Attention Assist 2 (AtAs)	●	●	●	●
Tyre Pressure Monitoring (TPM)	●	●	●	●
Active Brake Assist 6 Plus (ABA 6 Plus)	●	●	●	●
Front Collision Guard (FCG)	●	●	●	●
Sideguard Assist 2	●	●	●	●
Frontguard Assist	●	●	●	●

	Tourismo L	Tourismo M/3	Tourismo M/2	Tourismo
Traffic Sign Assist	●	●	●	●
Electronic Stability Program (ESP®)	●	●	●	●
MirrorCam	○	○	○	○
Reversing camera	●	●	●	●
Reversing buzzer	○	○	○	○
Extinguishing system	●	●	●	●
Rain-light sensor	●	●	●	●
Flat wiper blades with water fed through wiper blade	●	●	●	●
Rollover strength compliant with ECE-R 66.02	●	●	●	●

	Tourismo L	Tourismo M/3	Tourismo M/2	Tourismo
Weight and fuel tanks				
Capacity of fuel tank [l]	480	480	480	480
AdBlue® additive tank [l]	40	40	40	40
Gross vehicle weight [kg]	24,750	24,750	19,500	19,500
Axle loads, max. permissible front axle [kg]	7,500	7,500	7,500	7,500
Axle loads, max. permissible drive axle [kg]	12,600	12,600	12,600	12,600
Permissible weight trailing axle [kg]	5,750	5,750	-	-

	Tourismo L	Tourismo M/3	Tourismo M/2	Tourismo
Heating, air conditioning and ventilation				
Heater with convectors at side walls	●	●	●	●
Driver's area air conditioning	●	●	●	●
EvoCool Basic	●	●	●	●
EvoCool Comfort	○	○	○	○
EvoCool ComfortPlus	○	○	○	○
Cooling capacity passenger compartment [hp/kW]	39	35	32	32
Driver's area air conditioning [hp/kW]	8	8	8	8
Heating power passenger compartment [hp/kW]	39	39	36	36
Heating power driver's seat [hp/kW]	16	16	18	
Refrigerant filling capacity [lbs/kg]	7.5	7.5	6.5	6.5
CO ₂ equivalent [lbs/t]	10.725	10.725	9.295	13.585


	Tourismo L	Tourismo M/3	Tourismo M/2	Tourismo
Profitability				
Predictive Powertrain Control (PPC)	○	○	○	○
Tyre Pressure Monitoring (TPM)	○	○	○	○
Air resistance	0.33	0.33	0.33	0.33

	Tourismo L	Tourismo M/3	Tourismo M/2	Tourismo
Lighting				
Low beam	●	●	●	●
High beam	●	●	●	●
Daytime driving lights with LED technology	○	○	○	○
Daytime driving lights with halogen	●	●	●	●
Headlamps Bi-Xenon incl. cleaning system	○	○	○	○
Front fog lamp	●	●	●	●
Entrance lighting	●	●	●	●
Cornering light	○	○	○	○
Position lights	●	●	●	●
Ambient lighting luggage compartment	○	○	○	○
Ambient lighting for reverse driving	○	○	○	○
Ambient lighting for lift	○	○	○	○

● Standard equipment ○ Optional equipment * Optional equipment

SAFETY.

Sideguard Assist 2



Sideguard Assist 2 is a safety assistance system that supports the driver in critical situations when turning right or turning left when visibility is possibly restricted. The system is designed to help detect moving obstacles within the system limits, and warns the driver so as to avoid critical situations or reduce the consequences of accidents when turning off or changing lanes.


Electronic Stability Program (ESP®)

The Electronic Stability Program significantly reduces the risk of skidding by selectively braking individual wheels, thus preventing loss of control of the vehicle in curves and emergency steering manoeuvres.

Rain-light sensor

The rain sensor and automatic driving light are assist systems that activate automated functions by means of a sensor system and relieve the driver of routine tasks.

Electronic Braking Assist (BAS)



By constantly comparing the data, the electronic braking assist system immediately detects if the speed at which the brake pedal is pressed suddenly exceeds the usual level, and in such situations automatically boosts the maximum braking power to within fractions of a second. This significantly shortens the stopping distance of the vehicle.


AquaBlade® windscreen wipers

The AquaBlade® windscreen wipers ensure optimum visibility at all times and, thanks to an ergonomic design, minimise both driving noise and fuel consumption.

Acceleration Skid Control (ASR)

ASR prevents the drive wheels from spinning in two ways. On the one hand, ASR minimises wheel spinning through a measured braking intervention. On the other hand, the torque of the engine is regulated via the "electronic accelerator pedal".


Active Brake Assist 6 Plus



The ABA 6 Plus emergency braking system assists the driver by automatically initiating emergency braking if there is a risk of a rear-impact collision with vehicles in front or stationary obstacles. It can also detect moving or stationary persons and cyclists in front of the

vehicle. The system can respond with an audible and visual warning as well as automatic partial or full-stop braking.

Intelligent adaptive cruise control



The Adaptive Cruise Control feature (ACC) relieves the driver by maintaining a constant distance - defined by the driver - from the vehicle ahead, based on continuous measurements. This not only increases safety on country roads and motorways, but also convenience.

Front Collision Guard (FCG)



The unique Front Collision Guard (FCG) safety system protects the driver and passengers with state-of-the-

art, patented technology - uncompromisingly reliable in head-on collisions.

Lane Assist (SPA)



Lane Assist (SPA) detects when the vehicle unintentionally leaves a marked lane. If it crosses the markings, the driver is warned by a clear vibration through the driver's seat.

Tyre Pressure Monitoring (TPM)



Tyre Pressure Monitoring (TPM) displays the current pressure in the individual tyres and warns of deviations from the optimum pressure. This reduces tyre wear, has a positive effect on fuel consumption and prevents dangerous tyre damage.

MirrorCam

The modern MirrorCam system provides a clear and full view of the road traffic. Equipped with high-resolution cameras, the driving safety is improved and the risk of accidents is minimised. The extended field of vision enables the driver to see pedestrians, cyclists and other road users in the surrounding area. This eliminates the blind spot when turning right.

Traffic Sign Assist (TSA)



The innovative Traffic Sign Assist offers maximum safety and comfort on the road. Thanks to GPS and camera support, the vehicle speed is constantly compared with the current traffic regulations.

Frontguard Assist

Frontguard Assist is an advanced system that was specially developed to warn drivers of pedestrians located immediately in front of the vehicle and also to warn them of an impending accident. Whether you are pulling away or driving slowly (up to 9.3 mph), the intelligent assistance system can detect potential collisions with unprotected road users.

LEGAL NOTICES

Some of the product information, illustrations and images contained in this Digital Offering may have been prepared for generic use on Daimler Buses Digital Offerings maintained in different countries around the world. Consequently, some of the information and/or accessories which are not available in some countries or which, in order to satisfy local market demand or regulatory controls in such countries, may only be available in different specifications or configurations. If you are interested in any vehicle model, paint, option or accessory shown on the Internet site and are unsure of its availability or specification in your locality, you should contact Daimler Buses and/or a local authorised dealer for the relevant product, for information of current details in your locality.

All prices specified are recommended retail prices. Prices are current at the time of publication and subject to change without notice.

Provider: Daimler Buses GmbH, Fasanenweg 10, 70771 Leinfelden-Echterdingen, Germany

 and Mercedes-Benz are trademarks of Mercedes-Benz Group AG



03/2026