



THE CITARO.

Technical data and equipment at
a glance.

Mercedes-Benz

The standard for buses.



THE CITARO AT A GLANCE.

Citaro



Length [mm]:	12,135	Height [mm]:	3,095
Turning circle [mm]:	22,970	Width [mm]:	2,550

Citaro K



Length [mm]:	10,633	Height [mm]:	3,095
Turning circle [mm]:	17,284	Width [mm]:	2,550

Citaro LE



Length [mm]:	12,170	Height [mm]:	
Turning circle [mm]:	21,568	Width [mm]:	2,550

TECHNICAL DATA AND EQUIPMENT AT A GLANCE.

	Citaro	Citaro K	Citaro LE
Dimensions			
Length [mm]	12,135	10,633	12,170
Width [mm]	2,550	2,550	2,550
Width incl. mirrors [mm]	2,950	2,950	2,950
Height [mm]	3,095	3,095	3,095
Height incl. air-conditioning system [mm]	3.120/3.130	3.120 / 3.130	3.315 / 3.500
Height incl. optional equipment	3,300	3,300	3,500
Inner stand height [mm]	2,313	2,313	2,116
Inner stand height (top) [mm]	2,082	2,082	1,719
Parapet height (above ground) [mm]	952	952	952
Wheelbase front axle-drive axle [mm]	5,900	4,398	6,035
Wheelbase front axle-central axle [mm]	-	-	-
Wheelbase central axle-drive axle [mm]	-	-	-
Tyre size	275/70 R 22,5	275/70 R 22,5	275/70 R 22.5
Overhang at front [mm]	2,805	2,805	2,805
Overhang at rear [mm]	3,430	3,430	3,330
Turning circle [mm]	22,970	17,284	21,568
Turning circle BOKraft [mm]	25,000	25,000	25,000
Ring width turning circles min. [mm]	7,478	6,116	6,865
Ring width BOKraft [mm]	6,791	4,652	5,979
Ring width max. permissible according to BOKraft [mm]	7,200	7,200	7,200

	Citaro	Citaro K	Citaro LE
Track circle minimal [mm]	19,160	13,138	17,411
Wheel impact front axle max. [°]	53°/46°	53°/46°	53°/46°
Usable volume / capacity AdBlue [l]	27	27	27
Capacity fuel tank left / right [l]	260	260	260
Floor height over roadway [mm]	370	370	370
Pedestal height [mm]	310	310	310
Entry height door 1 [mm]	320	320	320
Entry height door 2 [mm]	320	320	320
Entry height door 3 [mm]	-	-	-
Entry height door 4 [mm]	-	-	-
Door opening width 1 [mm]	1,250	1,250	1,250
Door opening width 2 [mm]	1,250	1,250	1,250
Clear door width 3 [mm]	1,250	1,250	1,250
Clear door width 4 [mm]	-	-	-
Slope angle in front [°]	7	7	7
Slope angle rear [°]	7	7	7

	Citaro	Citaro K	Citaro LE
Transmission			
Engine	Mercedes-Benz OM 936 h / OM936	Mercedes-Benz OM 936 h / OM 936	Mercedes-Benz OM 936
Engine 2*	Mercedes-Benz OM 936 h / OM936	Mercedes-Benz OM 936 h / OM 936	Mercedes-Benz OM 936
Engine type	6-cylinder in-line engine	6-cylinder in-line engine	6-cylinder in-line engine
Output [kW]	220	220	220
Output 2* [kW]	260	260	260
Max. torque [Nm]	1,200	1,200	1,200
Max. torque 2* [Nm]	1,400	1,400	1,400
At speed [1/min]	1200 - 1.600	1200-1600	1.200 - 1.600
At speed 2* [1/min]	1200 - 1.600	1200-1600	1.200 - 1.600
Displacement [l]	7.7	7.7	7.7
Displacement 2* [l]	7.7	7.7	7.7
EU emissions standard	Euro VI	Euro VI	EURO VI
Hybrid system	○	○	○
Recuperation module	●	●	●
Transmission	Voith Diwa.6, 4-speed, automatic transmission	Voith Diwa.6	Voith Diwa.6, 4-speed, automatic transmission
Transmission 2*	Voith Diwa.6, 4-speed, automatic transmission	Voith Diwa.6	Voith Diwa.6, 4-speed, automatic transmission

	Citaro	Citaro K	Citaro LE
Chassis			
Steering	Power steering	Power steering	Power steering
Front axle, type	ZF RL82 EC	ZF RL 82 EC	ZF RL 82 EC
Centre axle, type	-	-	-
Driven axle, type	ZF AV 133	ZF AV 133	Mercedes-Benz RO 440
Front axle: independent suspension, anti-roll bar	●	●	●
Drive axle: with anti-roll bar	○	○	○
Raising/Lowering system	○	○	○
Kneeling	○	○	○
Articulation Turntable Controller (ATC)	-	-	-
Air suspension via electronic level control system (ENR)	●	●	●
Rough road running gear	○	○	○

	Citaro	Citaro K	Citaro LE
Brakes			
Pneumatic disc brakes on all axles	●	●	●
Electronic Stability Programme (ESP®)	○	○	○
Electronically controlled braking system (EBS)	●	●	●
Anti-locking system (ABS)	●	●	●
Acceleration Slip Regulation (ASR)	●	●	●
Retarder limiter (RL)	○	○	○
Retarder	●	●	●
Automatic bus stop brake with pull-away lock	●	●	●
Parking brake	●	●	●

	Citaro	Citaro K	Citaro LE
Safety and driver assistance systems			
Rollover strength compliant with in ECE R29	●	●	●
Tyre Pressure Monitoring (TPM)	●	●	●
Preventive Brake Assist 2	○	○	○
Front Collision Guard (FCG)	-	-	-
Sideguard Assist 2	●	●	●
Electronic Stability Program (ESP®)	○	○	○
Reversing camera	●	●	●
Reversing buzzer	○	○	○
Extinguishing system	●	●	●
Rain-light sensor	○	○	○
Flat wiper blades with water fed through wiper blade	●	●	●
Rollover strength compliant with ECE-R 66.02	●	●	●
360° Camera	○	○	○
270° Camera	-	-	-
Traffic Sign Assist	●	●	●
Frontguard Assist	●	●	●
Attention Assist 2 (AtAs)	●	●	●
MirrorCam	○	○	○

	Citaro	Citaro K	Citaro LE
Profitability			
Tyre Pressure Monitoring (TPM)	●	●	●

	Citaro	Citaro K	Citaro LE
Transport capacity			
Number of seats – standard seating	1/31	1/25	1/34
Passenger capacity max.	1/106	86	1/106
Seating type City Star Eco (CSE)	●	●	●
Seating type Inter Star Eco (ISE)	○	○	○
Seating type City Star Function (CSF)	○	○	○
Driver's seat GRAMMER Linea MSG 90.6 P, air-sprung	●	●	●
Driver's seat ISRI 6860, integrated pneumatic system, 3-point seat belt	○	○	○
Wheelchair space	○	○	○

	Citaro	Citaro K	Citaro LE
Weight and fuel tanks			
Capacity of fuel tank [l]	260	260	260
AdBlue® additive tank [l]	27	27	27
Gross vehicle weight [kg]	19,500	18,000	19,500
Axle loads, max. permissible front axle [kg]	7,500	7,245	7,500
Axle loads, max. permissible central axle [kg]	-	-	-
Axle loads, max. permissible drive axle [kg]	13,000	11,500	12,600

	Citaro	Citaro K	Citaro LE
Heating, air conditioning and ventilation			
Heater with convectors at side walls	○	○	○
Driver's area air conditioning	○	○	○
EvoCool Basic	○	○	○
EvoCool Comfort	○	-	-

	Citaro	Citaro K	Citaro LE
EvoCool ComfortPlus	<input type="radio"/>	-	-
Turbo roof ventilator	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
Roof-mounted air-conditioning system with heat pump	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Electric roof air conditioning (modular system)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Electric roof air conditioning system (modular system) for the driver's workstation	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Refrigerant filling capacity [lbs/kg]	0 - 10,5	0 - 8,5	0 - 9,5
CO ₂ equivalent [lbs/t]	0 - 15,015	0 - 12,155	0 - 13,585

	Citaro	Citaro K	Citaro LE
Doors and glazing			
Number of doors	2	2	2/3
Interior swivel door	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
Sliding swivel door	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Ramp manual	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Ramp electric	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Single glazed	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
Double glazed	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Windscreen heatable	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

	Citaro	Citaro K	Citaro LE
Lighting			
Low beam	●	●	●
High beam	●	●	●
Daytime driving lights with LED technology	○	○	○
Daytime driving lights with halogen	●	●	●
Headlamps with LED technology	○	○	○
Headlamps Bi-Xenon incl. cleaning system	○	○	○
Front fog lamp	○	○	○
Cornering light	○	○	○
Position lights	●	●	●

● Standard equipment ○ Optional equipment * Optional equipment

SAFETY.

Sideguard Assist 2

Sideguard Assist 2 is a safety assistance system that supports the driver in critical situations when turning right or turning left when visibility is possibly restricted. The system is designed to help detect moving obstacles within the system limits, and warns the driver so as to avoid critical situations or reduce the consequences of accidents when turning off or changing lanes.

Electronic Stability Program (ESP®)

The Electronic Stability Program significantly reduces the risk of skidding by selectively braking individual wheels, thus preventing loss of control of the vehicle in curves and emergency steering manoeuvres.

LED headlights for low beam and high beam

The vehicle is optionally equipped with long-life LED headlights. The light beam can be defined very accurately. The colour of the light is approximately the same as daylight, therefore the driver's eyes tire less quickly. More brightness and longer range provide additional safety.

Rain-light sensor

The rain sensor and automatic driving light are assist systems that activate automated functions by means of a sensor system and relieve the driver of routine tasks.

Electronic Braking Assist (BAS)

By constantly comparing the data, the electronic braking assist system immediately detects if the speed at which the brake pedal is pressed suddenly exceeds the usual level, and in such situations automatically boosts the maximum braking power to within fractions of a second. This significantly shortens the stopping distance of the vehicle.

AquaBlade® windscreen wipers

The AquaBlade® windscreen wipers ensure optimum visibility at all times and, thanks to an ergonomic design, minimise both driving noise and fuel consumption.

Acceleration Skid Control (ASR)

ASR prevents the drive wheels from spinning in two ways. On the one hand, ASR minimises wheel spinning through a measured braking intervention. On the other hand, the torque of the engine is regulated via the "electronic accelerator pedal".

Anti-lock Braking System (ABS)

The Anti-lock Braking System (ABS) supports driving stability during critical braking operations and ensures that the vehicle remains steerable. The braking forces acting on the individual wheels are distributed by the ABS so that even in an emergency braking situation no wheel is blocked for any length of time, and the steerability of the bus is largely maintained.

Preventive Brake Assist 2

With Preventive Brake Assist 2, Daimler Buses offers the second generation of Active Brake Assist. The system warns of collisions with moving pedestrians and cyclists as well as stationary and moving objects. In the event of a serious risk of collision, the driver is alerted by a visual and acoustic warning and partial braking is initiated automatically.

Articulation Turntable Controller (ATC)

Both agile and robust. The Articulation Turntable Controller (ATC) developed by Mercedes-Benz is a sophisticated anti-jackknife system for articulated buses. This swivel joint and its control system form one of the core components of the vehicle.

MirrorCam

The modern MirrorCam system enables a clear and comprehensive view of the road traffic. Equipped with high-resolution cameras, driving safety and the risk of accidents are minimised. The extended field of vision enables the driver to detect pedestrians, cyclists and other road users in the vicinity. This eliminates the blind spot when turning right.

Traffic Sign Assist (TSA)

The innovative Traffic Sign Assist offers maximum safety and comfort on the road. Thanks to GPS and camera support, the vehicle speed is constantly compared with the current traffic regulations.

Frontguard Assist

Frontguard Assist is an advanced system that was specially developed to warn drivers of pedestrians located immediately in front of the vehicle and also to warn them of an impending accident. Whether you are pulling away or driving slowly (up to 9.3 mph), the intelligent assistance system can detect potential collisions with unprotected road users.

Attention Assist (AtAs) 2

Attention Assist (AtAs) 2 is a safety assistance system that can help prevent microsleep. It thus contributes to improved driving safety, especially on long journeys and when driving at night. The system warns the driver visually and acoustically when it detects typical signs of overtiredness or inattention and prompts him/her to take a break. The warning is independent of the electronic logging device (ELD).

LEGAL NOTICES

Some of the product information, illustrations and images contained in this Digital Offering may have been prepared for generic use on Daimler Buses Digital Offerings maintained in different countries around the world. Consequently, some of the information and/or accessories which are not available in some countries or which, in order to satisfy local market demand or regulatory controls in such countries, may only be available in different specifications or configurations. If you are interested in any vehicle model, paint, option or accessory shown on the Internet site and are unsure of its availability or specification in your locality, you should contact Daimler Buses and/or a local authorised dealer for the relevant product, for information of current details in your locality.

All prices specified are recommended retail prices. Prices are current at the time of publication and subject to change without notice.

Provider: Daimler Buses GmbH, Fasanenweg 10, 70771 Leinfelden-Echterdingen, Germany

 and Mercedes-Benz are trademarks of Mercedes-Benz Group AG



04/2026